

# **SAP BCM 7.0 COMPATIBILITY LIST**

## **SAP BUSINESS COMMUNICATIONS MANAGEMENT SOFTWARE (SAP BCM)**

**Software version 7.0 SP5 and above**

19<sup>th</sup> of June 2013

© SAP AG



© Copyright 2013 SAP AG. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors.

- Microsoft, Windows, Outlook, and PowerPoint are registered trademarks of Microsoft Corporation.
- IBM, DB2, DB2 Universal Database, OS/2, Parallel Sysplex, MVS/ESA, AIX, S/390, AS/400, OS/390, OS/400, iSeries, pSeries, xSeries, zSeries, z/OS, AFP, Intelligent Miner, WebSphere, Netfinity, Tivoli, Informix, i5/OS, POWER, POWER5, OpenPower and PowerPC are trademarks or registered trademarks of IBM Corporation.
- Adobe, the Adobe logo, Acrobat, PostScript, and Reader are either trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.
- Oracle is a registered trademark of Oracle Corporation.
- UNIX, X/Open, OSF/1, and Motif are registered trademarks of the Open Group.
- Citrix, ICA, Program Neighborhood, MetaFrame, WinFrame, VideoFrame, and MultiWin are trademarks or registered trademarks of Citrix Systems, Inc.
- Hewlett-Packard is a registered trademark of Hewlett-Packard Company. (Hewlett-Packard®)
- HP is a registered trademark of Hewlett-Packard Company. (HP®)
- HTML, XML, XHTML and W3C are trademarks or registered trademarks of W3C®, World Wide Web Consortium, Massachusetts Institute of Technology.
- Java is a registered trademark of Sun Microsystems, Inc.
- JavaScript is a registered trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape.
- MaxDB is a trademark of MySQL AB, Sweden.

SAP, R/3, mySAP, mySAP.com, xApps, xApp, SAP NetWeaver, and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and in several other countries all over the world. All other product and service names mentioned are the trademarks of their respective companies. Data contained in this document serves informational purposes only. National product specifications may vary.

These materials are subject to change without notice. These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.


---

## 1 SAP BCM compatibility list – certified devices

Certified indicates that SAP Labs Finland or a technology partner has tested the device and that SAP Labs Finland proactively strives to maintain the compatibility. Compatible device means that the device can be used with BCM but it does in no way mean that BCM supports all the features of the device, such as video calls, various indicators, multiline (e.g. mobile and PC) support and others.

## 1.4 SIP desk phones

Listed SIP phones perform the following operations properly with BCM: register, inbound call, outbound call, hold, transfer and sending DTMF. The operations work using any of the transport protocols UDP, TCP or TLS. Exceptions and prerequisites or other requirements may be included in table. Additional features present on the phone may or may not work. See SAP Note 1872998 for configuring hold formats.

Innovaphone		IP232	IP222	IP241	IP240	IP110
Admin	TFTP (log/conf./update)	C/U	C/U	C/U	C/U	C/U
	Web administration	●	●	●	●	●
	Minimum version	10	10	10	10	10
Time & date	NTP client	●	●	●	●	●
	Time zone	●	●	●	●	●
	Daylight savings	●	●	●	●	●
Phone	Number of lines	6	6	6	6	6
	Function keys	2 x 6	2 x 6	7 + 8	7 + 8	4
	Speaker	HD speaker	HD speaker	●	●	●
	Display	Color 480 x 272 touch screen	Color 320 x 240	Color 320 x 240	Black/White 128 x 64	Black/White
	Keyboard	In-Screen Alphanumeric	Numeric	Alphanumeric	Alphanumeric	Numeric
	Multi-language	16	16	16	16	16
Voice	PCMA	●	●	●	●	●
	PCMU	●	●	●	●	●
	G.729	●	●	●	●	●
Network	Ethernet	2 x GigE	2 x GigE	2 x GigE	2 x 10/100	2 x 10/100
	LAN/PC port	●	●	●	●	●
	Power over Ethernet	●	●	●	●	●
	DHCP client	●	●	●	●	●
	VLAN	●	●	●	●	●
	Voice QoS					
Security	HTTPS	●	●	●	●	●
	TLS	●	●	●	●	●
	SRTP	●	●	●	●	●
	SIP authentication	●	●	●	●	●
Notes		Design-price awarded	Design-price awarded			
		 reddot design award winner 2011	