



Technical Data



Product description:

- Wall mountable housing for DECT base station models IP1202e/1203e including thermostat-controlled trace heating 150W

Product characteristics:

- Fully insulated in accordance with VDE 100 § 7
- 2.5 - 3.5 mm impact-resistant, glass fibre-reinforced unsaturated polyester
- Self-extinguishing in accordance with ASTM D 635 or UL 94 VO
- Temperature-resistant between -30° and 150°C
- Suitable for outdoor installation and in aggressive ambient conditions
- Degree of protection IP 66
- Door with double seal at the top and bottom edge of the door
- Door with foamed-in seal
- Door opening angle 130° according to VDI
- Sash lock with double bar insert in accordance with DIN 43668
- 2 M20 cable glands
- Pre-assembled UAE socket AP 8/8
- Mounting bracket for base station
- Bypass terminals (clamping range 1.52 to 42 mm) with integrated fuse holder and contact protection cover
- Fuse protection: 6A T miniature fuse
- Heating capacity 150W
- Thermostat set to 0 to 5 degrees Celsius sealed

Colour:

- light grey similar to RAL 7032, recoatable

External size (Width x Height x Depth):

- 400 x 400 x 200 mm, without wall mounting
- Right door hinge

Weight:

- Approx. 10kg

Orderno.: 50-01202-008